

**M-D-STRIPAX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- Flexible and solid wire with PVC, Teflon (PTFE) and silicone insulation
- No damage to the wire thanks to specially shaped blade
- No splicing of individual wires
- Blade inserts are easy to replace
- All inserts fit one housing
- Guide bars in the blade cassettes facilitate correct positioning of the wire in the tool

**General ordering data**

Version	Tools, Stripping and cutting tool
Order No.	<a href="#">9001280000</a>
Type	M-D-STRIPAX
GTIN (EAN)	4008 1900 11215
Qty.	1 pc(s).

Creation date March 15, 2022 2:48:15 PM CET

Catalogue status 11.03.2022 / We reserve the right to make technical changes.

**M-D-STRIPAX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	16 mm	Depth (inches)	0.63 inch
Height	135 mm	Height (inches)	5.315 inch
Width	82 mm	Width (inches)	3.228 inch
Weight	110 g	Net weight	122 g

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

**Technical data**Description of article Stripping tool for up to 1 mm<sup>2</sup> for PVC/silicone**Stripping tools**

Cable type	Flexible and solid conductors with PVC insulation	Conductor cross-section, max.	1 mm <sup>2</sup>
Conductor cross-section, min.	0.08 mm <sup>2</sup>	Max. conductor diameter	1.3 mm
Min. conductor diameter	0.3 mm	Stripping length, max.	7 mm
Stripping range AWG, max.	18 AWG	Stripping range AWG, min.	28 AWG
Stripping range, min.	0.08 mm <sup>2</sup>		

**Classifications**

ETIM 6.0	EC002109	ETIM 7.0	EC002109
ETIM 8.0	EC002109	ECLASS 9.0	21-04-37-06
ECLASS 9.1	21-04-37-06	ECLASS 10.0	21-04-37-06
ECLASS 11.0	21-04-37-06		

**Downloads**Catalogues [Catalogues in PDF-format](#)

Brochures

**M-D-STRIPAX**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Example of use**

