


NDTP30RT
Data
Ordering data

| | |
|-------------------------------|---------------|
| Product type description | NDTP30RT |
| Article number (order number) | 103005362 |
| EAN (European Article Number) | 4030661434841 |
| eCl@ss number, Version 9.0 | 27-37-12-10 |

Certifications

| | |
|--------------|--------------|
| Certificates | cULus IPA |
|--------------|--------------|

General data

| | |
|---------------------------------|-----------------------------------|
| Product name | Mushroom button NDTP |
| Standards | EN 60947-5-1 IEC/EN 60947-1 |
| Versions | round Mushroom button Round |
| Sealing type | Membrane Lip gaskets |
| Material of the operators | Plastic |
| Material of the front ring | ABS, chrome-plated |
| Material of the bellows | Silicone |
| Colour of the operating element | Red |
| Colour of the front ring | Silver |
| Colour of the bellows | White |
| Gross weight | 36 g |

General data - Features

| | |
|------------------|-----|
| Mounting flange | Yes |
| Probing possible | Yes |
| Fully insulated | Yes |

Mechanical data

| | |
|--------------------------------|---------------------|
| Mounting | Mounting flange EFM |
| Actuating stroke | 5 mm |
| Tightening torque of the screw | 0.6 Nm |

Mechanical data - Dimensions

| | |
|--|---------------|
| Height | 20 mm |
| diameters for the actuating heads | 30 mm |
| Diameter hole | 22.3 mm |
| Diameter hole, with tolerance indication | 22.3 + 0.4 mm |
| Thickness, of the front panel, minimum | 1.5 mm |
| Thickness of the front panel, maximum | 6 mm |
| Spacing | 50 x 50 mm |

Ambient conditions

| | |
|------------------------------|---------------|
| Protection class | IP67 IP69K |
| Ambient temperature, minimum | -25 °C |
| Ambient temperature, maximum | +80 °C |

Documents

Operating instructions and Declaration of conformity

(1,3 MB, 10.05.2019, Revision B)

BG-test certificate

(286,7 kB, 28.04.2020)

UL Certificate

(413,7 kB, 01.08.2019)

IPA Data

(242,8 kB, 10.05.2019, Revision A)

Brochure

(8,7 MB, 10.05.2019, Revision 03)

Pictures

Product picture (catalogue individual photo)



ID: kndtpf03

| 34,4 kB | .png | 74.083 x 74.083 mm - 210 x 210
Pixel - 72 dpi

| 53,3 kB | .jpg | 27.093 x 27.093 mm - 320 x 320 Pixel
- 300 dpi

| 391,4 kB | .jpg | 352.778 x 352.778 mm - 1000 x
1000 Pixel - 72 dpi

System components

EFMH/SEK - Mounting flange for position switch



101014388 EFM

- mounting flange with Position switch
- 30 mm x 42 mm x 92 mm
- Thermoplastic enclosure

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 23.06.2020 11:47:56