


291a

Plug, plain, solid




solid

Dimension	Code	b	s
S 3/4	770 292 105	28	17
V 3/4	770 292 205		
S 1	770 292 106	33	19
V 1	770 292 206		
S 1 1/4	770 292 107	36	22
V 1 1/4	770 292 207		
S 1 1/2	770 292 108	38	23
V 1 1/2	770 292 208		
S 2	770 292 109	44	27
V 2	770 292 209		

294

Plug with hole in the square




Dimension	Code	c	s
S 1/2	770 294 104	32	11
V 1/2	770 294 204		
S 3/4	770 294 105	37	17
V 3/4	770 294 205		
S 1	770 294 106	44	19
V 1	770 294 206		
S 1 1/4	770 294 107	43	22
V 1 1/4	770 294 207		
S 1 1/2	770 294 108	44	22
V 1 1/2	770 294 208		
S 2	770 294 109	53	27
V 2	770 294 209		

300

Cap

iso T1



Dimension	Code	a	s
• S 1/8 □	770 300 101	14	14
• V 1/8 □	770 300 201		
• S 1/4 □	770 300 102	17	17
• V 1/4 □	770 300 202		
• S 3/8 □	770 300 103	18	22
• V 3/8 □	770 300 203		
• S 1/2	770 300 104	24	26
• V 1/2	770 300 204		
• S 3/4	770 300 105	26	32
• V 3/4	770 300 205		
• S 1	770 300 106	29	38
• V 1	770 300 206		
• S 1 1/4	770 300 107	32	47
• V 1 1/4	770 300 207		
• S 1 1/2	770 300 108	32	53
• V 1 1/2	770 300 208		
• S 2	770 300 109	37	66
• V 2	770 300 209		
• S 2 1/2	770 300 110	41	83
• V 2 1/2	770 300 210		
• S 3	770 300 111	44	96
• V 3	770 300 211		
• S 4	770 300 112	52	128
• V 4	770 300 212		