


# ABSOLUTE Digimatic Thickness Gauge

Series 547

For measuring film, paper, etc., with a resolution of 0,001 mm.



547-401



## Metric

No.	Range [mm]	Digital step	Indicator No.	Max. measuring depth [mm]	Mass [g]
547-401	0-12	0,01 mm/0,001 mm	543-390BS (ID-C)	21	290



Functions	Series 547
ZERO/ABS	●
GO/±NG judgement	●
Digimatic data output	●
ON/OFF	●
DATA/HOLD	●
Lock function	●
PRESET	●
Counting direction switchable	●
Calculation function	●

## Specifications

Accuracy	±4 μm (excluding quantizing error)
Measuring force	≤ 3,5 N
Scale	Capacitance type ABSOLUTE linear encoder
Parallelism	3 μm
Max. response speed	Unlimited
Contact point	M 2,5 x 0,45 mm (ISO/JIS type)
Alarm	Low voltage, counting value composition error, overflow error, tolerance limit setting error
Power supply	1 battery SR-44
Battery life	approx. 7.000 hours

## Optional accessories

No.	Description
905338	Digimatic cable (1 m)
905409	Digimatic cable (2 m)
06ADV380F	USB Input Tool Direct cable (2 m)
02AZD790F	Connecting cable U-Wave

## Consumable spares

No.	Description
938882	Battery SR44
21AZB149	Lifting lever


# QUICK MINI Thickness Gauge

Series 700

This is a lightweight, palm-sized thickness gauge.



700-119-20



## Metric

No.	Range [mm]	Digital step	Mass [g]
700-119-20	0-12	0,01 mm	70



Functions	Series 700
ORIGIN	●
ZERO/ABS	●
ON/OFF	●

## Specifications

Accuracy	±0,02mm (excluding quantizing error)
Measuring force	2 N
Power supply	Battery SR-44
Display	LCD, Character height 9 mm
Battery life	approx. 20.000 hours
Delivered	In case

## Consumable spares

No.	Description
938882	Battery SR44