

KT 12**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

| | |
|------------|--|
| Version | Cutting tools, Cutting tool for one-hand operation |
| Order No. | 9002660000 |
| Type | KT 12 |
| GTIN (EAN) | 4008190181970 |
| Qty. | 1 pc(s). |

Creation date March 15, 2022 12:39:16 PM CET

Catalogue status 11.03.2022 / We reserve the right to make technical changes.

KT 12

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|--------|---------|-----------------|------------|
| Depth | 30 mm | Depth (inches) | 1.181 inch |
| Height | 63.5 mm | Height (inches) | 2.5 inch |
| Width | 225 mm | Width (inches) | 8.858 inch |
| Weight | 300 g | Net weight | 331.7 g |

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data

| | | | |
|------------------------|---|---------|---------------------|
| Description of article | Cutting tool for up to 12 mm outer diameter | Version | One-hand mechanical |
|------------------------|---|---------|---------------------|

Cutting tools

| | | | |
|---|--------------------|--|--------------------|
| Copper cable - flexible, max. | 35 mm ² | Copper cable - flexible, max. (AWG) | 2 AWG |
| Copper cable - solid, max. | 16 mm ² | Copper cable - solid, max. (AWG) | 6 AWG |
| Copper cable - stranded, max. | 25 mm ² | Copper cable - stranded, max. (AWG) | 3 AWG |
| Copper cable, max. diameter | 12 mm | Data / telephone / control cable, max. Ø | 12 mm |
| Single-core aluminium cable, max.(mm ²) | 25 mm ² | Stranded aluminium cable, max (mm ²) | 25 mm ² |
| Stranded aluminium cable, max. (AWG) | 6 AWG | Stranded aluminium cable, max. diameter | 8 mm |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000142 | ETIM 7.0 | EC000142 |
| ETIM 8.0 | EC000142 | ECLASS 9.0 | 21-04-47-01 |
| ECLASS 9.1 | 21-04-37-06 | ECLASS 10.0 | 21-04-47-01 |
| ECLASS 11.0 | 21-04-47-01 | | |

Approvals

Approvals



Downloads

| | |
|---|--|
| Approval/Certificate/Document of Conformity | Manufacturer's Declaration - Cable cutters |
| Catalogues | Catalogues in PDF-format |
| Brochures | |

KT 12

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Example of use

