

T2FH232-22UEDR/22UEDR

- **double-pedal type**
- **2 cable entries M25**
- **High level of stability**
- **Protective shield with wide opening**

Data

Certifications

Certificates	cULus CCC EAC
--------------	---------------------

General data

Product name	T2FH 232
Standards	EN 60947-5-1 DIN VDE 0660-200 BG-GS-ET-15
Enclosure material	Aluminium
Enclosure coating material	powder-coated
Material of the cover	Aluminium
Material of the pedal	Glass-fibre, reinforced thermoplastic
Material of the protective shield	Aluminium
Gross weight	4057.000 g

General data - Features

Latching	Yes
Protective shield	Yes
Probing possible	Yes
Suitable for EMERGENCY-OFF	Yes
Number of pedals, NC	2
Number of pedals, NO	2

Safety appraisal

Standards	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	100,000 Operations
-----------------------------------	--------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
--------------------------	----------------------

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Width	295 mm
Height	189 mm
Depth	274 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Relative humidity, minimum	30 %
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing non-icing
Resistance to vibrations to EN 60068-2-6	10 ... 150 Hz (0.35 mm / 5 g)
Restistance to shock	30 g / 11 ms

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV III
Degree of pollution to VDE 0100	3

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Slow action with overlapping contacts
Switching frequency	3,600 /h

Pictures

Product picture (catalogue individual photo)



ID: ktfh2f02


| 23,5 kB | .png | 74.083 x 49.389 mm - 210 x 140

Pixel - 72 dpi

| 252,3 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667

Pixel - 72 dpi

Dimensional drawing basic component



ID: 1t2f-g03

| 12,7 kB | .png | 74.083 x 51.858 mm - 210 x 147


Pixel - 72 dpi

| 166,7 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

| 47,0 kB | .cdr |


Diagram



ID: ktf--k12


| 17,9 kB | .cdr |

Operating principle



0

ID: ktf--a01




I

| 21,6 kB | .png | 74.083 x 111.125 mm - 210 x 315
Pixel - 72 dpi



| 220,4 kB | .jpg | 352.778 x 529.872 mm - 1000 x
1502 Pixel - 72 dpi



→ 0

| 36,3 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 26.08.2020 12:51:15