



**Short version**  
**Float in PVDF with magnet**  
**With solvent cement sockets PVC-U metric**

**Model:**

- Suitable limit switches see accessories for variable area flow meters
- Union nuts and valve ends in other materials on request

Scale range (L/h)	Type	d (mm)	DN (mm)	Taper tube in Polysulfone O-rings in EPDM Code	Weight (kg)	Taper tube in PVC-U transp. O- rings in EPDM Code	Weight (kg)
2.5 - 25.0	SK 500	16	10	<b>198 801 890</b>	0.079	<b>198 803 320</b>	0.081
5.0 - 50.0	SK 510	16	10	<b>198 801 891</b>	0.102	<b>198 803 321</b>	0.080
10.0 - 100.0	SK 520	16	10	<b>198 801 892</b>	0.075	<b>198 803 322</b>	0.079
8.0 - 80.0	SK 600	20	15	<b>198 801 893</b>	0.123	<b>198 803 323</b>	0.129
15.0 - 150.0	SK 610	20	15	<b>198 801 894</b>	0.121	<b>198 803 324</b>	0.128
20.0 - 200.0	SK 620	20	15	<b>198 801 895</b>	0.119	<b>198 803 325</b>	0.125
15.0 - 150.0	SK 700	32	25	<b>198 801 896</b>	0.248	<b>198 803 326</b>	0.301
30.0 - 300.0	SK 710	32	25	<b>198 801 897</b>	0.289	<b>198 803 327</b>	0.255
50.0 - 500.0	SK 720	32	25	<b>198 801 898</b>	0.241	<b>198 803 328</b>	0.248
100.0 - 1000.0	SK 730	32	25	<b>198 801 899</b>	0.280	<b>198 803 329</b>	0.242

Scale range (L/h)	Type	D (mm)	L (mm)	L1 (mm)	L2 (mm)	G (inch)
2.5 - 25.0	SK 500	35	199	171	165	¾
5.0 - 50.0	SK 510	35	199	171	165	¾
10.0 - 100.0	SK 520	35	199	171	165	¾
8.0 - 80.0	SK 600	43	223	191	185	1
15.0 - 150.0	SK 610	43	223	191	185	1
20.0 - 200.0	SK 620	43	223	191	185	1
15.0 - 150.0	SK 700	60	250	206	200	1 ½
30.0 - 300.0	SK 710	60	250	206	200	1 ½
50.0 - 500.0	SK 720	60	250	206	200	1 ½
100.0 - 1000.0	SK 730	60	250	206	200	1 ½

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>