

**Industrial Ethernet
IE-PS-RJ45-FH-BK**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



RJ45 plug-in connector (tool-less) according to IEC 60603-7-51 for wire outer diameters up to 1.6 mm

General ordering data

Type	IE-PS-RJ45-FH-BK
Order No.	1963600000
Version	RJ45 plug, no tools required, Cat.6 _A / Class E _A (ISO/IEC 11801 2010), 8-core, 4-core, EIA/TIA T568 A, EIA/TIA T568 B, PROFINET
GTIN (EAN)	4032248645725
Qty.	10 pc(s).

Industrial Ethernet IE-PS-RJ45-FH-BK

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technische Daten

Dimensions and weights

Net weight 27.5 g

Temperatures

Operating temperature -40 °C...70 °C Storage temperature
Installation temperature

Downloads

Attestation of conformity ISO/IEC EN & TIA/EIA Screened Class EA Category 6A, 4 connector channel	z1755b-07-E.pdf	CC-Link certification	CC-Link IE-PS-RJ45-FH-BK.PDF
GOST Approval	POCC DE.ME25.B01411.pdf	Installation video	STEADYTEC® assembly instruction RJ45 field attachable connector _EN_640_480.mp4
PROFINET Manufacturer's Declaration	PN Manufacturer Declaration.pdf	UL Approval	DUXR.E316369.pdf

General data

Ability to reconnect	≥ 10 cycles (for the same or larger cross-section)	Category	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)
Configuration	Eight-wire field-assembled RJ45 plug with colour coding on the plug, TIA A/B/ProfiNet, multiport-ready	Connection 1	RJ45
Connection 2	IDC	Contact material	Phosphorus bronze
Contact surface	Gold over nickel	Housing main material	Zinc diecast
Insertion force	≤ 30 N	Insulation cross-section, max.	1.6 mm
Insulation cross-section, min.	0.85 mm	MICE classification C	C ₁
MICE classification E	E ₃	MICE classification I	I ₁
MICE classification M	M ₁	Plugging cycles	750
Protection degree	IP 20	Sheath diameter, max.	8.5 mm
Sheath diameter, min.	5.5 mm	Shielding	360° all-round enclosure
Speed	10 GBit	Wire connection diameter, flexible, max.	0.76 mm
Wire connection diameter, flexible, min.	0.48 mm	Wire connection diameter, solid, max.	0.64 mm
Wire connection diameter, solid, min.	0.4 mm	Wire cross-section, finely stranded, max. (AWG)	AWG 22
Wire cross-section, finely stranded, min. (AWG)	AWG 26	Wire cross-section, solid, max. (AWG)	AWG 22
Wire cross-section, solid, min. (AWG)	AWG 24	Wiring	8-core, 4-core, EIA/TIA T568 A, EIA/TIA T568 B, PROFINET

Electrical properties

Contact resistance	≤ 20 mΩ	Current-carrying capacity at 50 °C	1 A
Dielectric strength, contact / contact	≥ 1000 V DC	Dielectric strength, contact / shield	≥ 1500 V DC
Insulation resistance	> 500 MΩ	PoE / PoE+	conforming to IEEE 802.3at

Datenblatt

**Industrial Ethernet
IE-PS-RJ45-FH-BK**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Standards

Generic communication cable facilities	ANSI / TIA / EIA-568-B.2-10, DIN EN 61918 Draft 02.2007, ISO / IEC 11801:2002, ISO / IEC 24702:2006	Application-specific communication cable facilities	PROFINET installation instructions
IP protection classes	IEC 60529	Connector standard	IEC 60603-7-51
UL standard for communication accessories	UL 1863	Certificate no. (cULus)	E316369

Classifications

ETIM 3.0	EC001121	UNSPSC	30-21-18-10
eClass 5.1	27-26-07-08	eClass 6.2	27-25-05-04
eClass 7.1	27-25-05-04		

Approvals

Approvals



ROHS Conform

Datenblatt

**Industrial Ethernet
IE-PS-RJ45-FH-BK**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Zeichnungen

Printing



Dimensioned drawing

