

Portable Surface Roughness Tester Surftest SJ-210/310 Series



Portable Surface Roughness Tester

Surftest SJ-210/310 Series

Compact but Highly Functional

Surface roughness tester with refined user-friendliness that has been highly rated by customers over the years.

Surftest SJ-210 Series


.....
Exceptionally convenient compact surface roughness testers that can be carried around like handheld tools, or used on sites.



*More than 20 years from the launch of the **SJ Series!**
They have been pioneers of compact surface roughness testers.
With overwhelming performance, they contribute to manufacturing all over the world.*

Surftest SJ-310 Series

Compact surface roughness testers that not only provide both diverse measuring/analytical functions and excellent portability, but also have built-in printers.



Solve Your Problems with the **SJ-210/310 Series!**

Case 1



Got an old model?

I wish I could visually check roughness during a measurement.

And, is there any way to print the measurement results faster?

Case 2



Got a fixed installation type surface roughness measuring machine?

Carrying workpieces to the inspection room is hard!

And, is there any way to measure different surfaces on the workpiece without moving it around?

Case 3



Don't own a surface roughness measuring machine?

Measuring roughness seems difficult...

Can I do it myself?



With the SJ-210/310 Series...

You can measure while checking roughness from the waveform!

Printing completes in just a few seconds! (SJ-310)



With the SJ-210/310 Series...

No need to carry large, heavy workpieces because you can measure on site!

Lightweight and compact, you can measure any side without trouble!



With the SJ-210/310 Series...

With skidded measurement*, anyone can measure easily!

* Measurement method where leveling of the measurement surface is simplified since displacement is measured relative to the "skid" that follows the workpiece surface.



So easy that anyone can use it!

Reduces data input labor significantly

Measurement Data Wireless Communication System

U-WAVE (optional)



Example of SJ-210 installation



Example of SJ-310 installation

“U-WAVE” is a system that allows measured parameter values to be imported to commonly used software (Excel, notepad, etc.) at the touch of a button. Being wireless, it does not affect the operability during measurement, and contributes to reducing data input labor and error, thereby improving work efficiency.



U-WAVE-R
(Connects to the PC)
02AZD810D



U-WAVE-T*
(Connects to the SJ-210/310 Series)
02AZD880G
* Requires the optional connection cable.
02AZD790D

Input at the touch of a button

USB INPUT TOOL (optional)

An interface to output the calculation results of the SJ-210/310 Series via USB to spreadsheet software on PC. Allows you to input the calculation results (numerical values) at the touch of a button.



USB Input Tool-Direct
USB-ITN-D
06AFM380D



USB keyboard signal conversion type*
IT-016U
264-016-10
* Requires the optional connection cable.
1 m: **936937**
2 m: **965014**

Advanced free software!


Further improve convenience by linking with a PC

Simplified communication program for SURFTEST



Introduction video available here.

The program can not only start a measurement or change measurement conditions from a PC, but also create inspection record tables using Microsoft Excel macros. Allows you to operate **SJ-210/310 Series** more conveniently and significantly reduce the time for creating reports.



This program can be downloaded free of charge from the Mitutoyo website.
<https://www.mitutoyo.co.jp>

Required environment

- OS: Windows 7
 - OS: Windows 8
 - OS: Windows 10
 - Spreadsheet software: Microsoft Excel 2010
 - Spreadsheet software: Microsoft Excel 2013
 - Spreadsheet software: Microsoft Excel 2016
 - Spreadsheet software: Microsoft Excel 2019
 - Spreadsheet software: Office365 ProPlus (Windows10 Pro)
- Note: Windows OS, Microsoft Excel and Office365 ProPlus are products of Microsoft Corporation.

The optional USB cable is also required.

- USB cable for **SJ-210 Series** (2 m)
12AAL068
 Note: Commercially available USB Mini Type B cable or equivalent
- USB cable for **SJ-310 Series**
12AAD510
 Note: Commercially available USB Type B cable or equivalent

Optional combinations!

Improve work efficiency by utilizing diverse options

Contour/Roughness analysis software FORMTRACEPAK-AP

Data collected by the **SJ-210/310 Series** can be loaded to **FORMTRACEPAK-AP**, a form assessment/analysis software package, via a memory card (optional) for more advanced analysis.

Digimatic mini processor DP-1VA LOGGER

By connecting this printer to the SurfTest **SJ-210/310 Series'** digimatic output, you can print* calculation results, perform a variety of statistical analyses, draw a histogram or D chart, and also perform complicated operations for X-R control charts.

* The symbol 'µm' is not printable, but measurement results can still be printed out without setting the measurement unit.



264-505

- **SJ-210/310 Series** → **DP-1VA LOGGER** Connecting cable
- 1 m: 936937
- 2 m: 965014

Foot switch

Allows starting and stopping of measurement just by tapping. Allows you to significantly increase efficiency in measurements where large numbers of the same workpiece are fixed and measured in one go.



12AAJ088

Memory card (2 GB)



12AAW452


- Note 1: micro SD card (with a conversion adapter to SD card)
- Note 2: Not all memory cards can be recognized. Please use the optional SD memory card.

SJ-210/310 Series 6 Convenient Functions

Enhance versatility by linking tester capabilities!

- SJ-210/310 Linkage -

"Measuring with the compact and easy-to-carry SJ-210, while analyzing and printing with the highly functional SJ-310" is a recommended scenario.



Avoid "careless mistakes", such as forgetting to save or erroneously deleting data. - Trace 10 -

Enables displaying of the past 10 automatically saved calculation results. Allows for immediately checking of "recent numerical values" that you just cannot recall.




Note: Requires a memory card (optional).



Just choose the assessment conditions from the list. Comfortably, without the need to scroll! - Single-screen parameter list -

Expressive color graphic LCD. Specify settings easily on a single screen, without scrolling. Chosen parameters are easily identifiable by their different background and letter color.



Parameter setting on SJ-210



Parameter setting on SJ-310

No need to worry about hard-to-see points. Reliable measurement by contact detection.

- Contact status Screen display -

"Red: No contact" and "Blue: Contact", hence the detector contact status can be reliably judged.



Display of SJ-210



When there is no contact



When there is contact

Display of SJ-310



When there is no contact




When there is contact

With a stabilizer, no more erroneous measurements.

- Self-timer -

No need to worry about erroneous measurements due to vibration since measurement can be started after the vibration subsides.



Using passwords means less worries for administrators!

- Function restriction -

Allows locking of optional items, such as measurement and calibration conditions.
Prevents erroneous measurements due to a careless setting change or accidental operation.



Password setting



SJ-210 Series Other Functions

Outstanding visibility! 2.4-inch color graphic LCD

Clear, easy-to-read, large screen with backlight.

GO/NG judgment screen designed with emphasis on ease-of-comprehension

Results can be clearly determined at a glance since pass and fail are indicated in different colors.

2020/09/28		SPC	
ISO1997	0.5 mm/s	λc 0.8	x5
Ra	0.664	μm	OK
Rq	0.808	μm	+NG
Rz	3.767	μm	+NG
Rp	1.866	μm	-NG

Operation keys with consideration given to ease-of-use and prevention of accidental operation

Frequently used keys are arranged on the top surface of the main unit.

Seldom used keys are arranged inside the cover to prevent accidental operation.



Shortcuts that enable intuitive operation

Display settings can be easily changed by operating the [←] and [→] keys inside the cover. For example, cutoff value (λ_c) and number of segments (N) can be easily switched on the measurement screen.



With a carrying case, easy to carry around

Convenient, dedicated case for comfortable carrying (Standard accessory)



High-speed measurement data transmission

Equipped with several I/O ports, including a high-speed USB interface, as standard.



Printer for SJ-210 (optional)

Assessed profiles and calculation results and curves can be printed out by connecting the SJ-210-dedicated printer, which is palm sized (WxDxH: 93x125x70 mm) and can run on an internal battery.

- Power supply can be selected. (AC adapter or battery pack)
- Printable items: Measurement conditions, calculation results, assessed profile, bearing area curve (BAC), amplitude distribution curve (ADC), and environment settings.



Example of the output by the printer

Printer supplies:

- Printing paper standard type (5 rolls) 270732
- Durable printer paper (5 rolls) 12AAA876

178-421

Surftest SJ-210 Series

SJ-310 Series Other Functions



Supports measurement with outstanding visibility on the large 5.7-inch color graphic LCD

The large-screen LCD comes with a touch-panel. High operability makes measurement smooth.


With a built-in high-speed printer, allows printing measurement results anytime and anywhere

All processes from measuring to printing the measurement results can be completed just by pressing a single button. Printing takes just a few seconds!



Simultaneous two-curve assessment function that enables advanced utilization of measurement data

Allows acquisition of calculation and analysis results according to two different assessment conditions from one measurement.




Delete function that widens the utilization range of the data

Allows calculation by partially deleting abnormal results, such as cracks.




Coordinate difference analysis that promptly picks up the workpiece status

Allows calculation of the coordinate difference between two waveform points.
Allows checking of workpiece unevenness on the screen, without printing.



Statistical processing that helps data management

Capable of up to 300 statistical measurements for a maximum of three parameters, enabling routine data to be appropriately managed.



Condition inputting possible in drawing instruction format

Also allows for assessment condition inputting using drawing instruction symbols compliant with ISO/JIS roughness standards.

Surftest SJ-310 Series

SJ-210 Series Specifications

Type of detector	Standard drive unit type		Retractable drive unit type		Transverse tracing drive unit type		
Model No.	SJ-210 (0.75 mN type)	SJ-210 (4 mN type)	SJ-210 (0.75 mN type)	SJ-210 (4 mN type)	SJ-210 (0.75 mN type)	SJ-210 (4 mN type)	
Order No.	mm	178-560-11	178-560-12	178-562-11	178-562-12	178-564-11	178-564-12
	inch/mm	178-561-11	178-561-12	178-563-11	178-563-12	178-565-11	178-565-12
X axis	16.0 mm				5.6 mm		
Measuring range	Range	360 μm (-200 μm to +160 μm)					
	Z axis (Detector)	360 μm/0.02 μm					
		Range/ Resolution	100 μm/0.006 μm 25 μm/0.002 μm				
Measuring speed	When measuring: 0.25 mm/s, 0.5 mm/s, 0.75 mm/s When returning: 1 mm/s						
Measuring force/Stylus tip	0.75 mN type: 0.75 mN/2 μmR 60°, 4 mN type: 4 mN/5 μmR 90°						
Skid force	400 mN or less						
Applicable standards	JIS '82/JIS '94/JIS '01/ISO '97/ANSI/VDA						
Assessed profiles	Primary profile, Roughness profile, DF profile, Roughness profile-Motif						
Parameters	Ra, Rc, Ry, Rz, Rq, Rt, Rmax ^{*1} , Rp, Rv, R3z, Rsk, Rku, Rc, RPC, Rsm, Rz1max ^{*2} , S, HSC, Rz1S ^{*3} , Rppi, R Δ a, R Δ q, Rlr, Rmr, Rmr(c), R δ c, Rk, Rpk, Rvk, Mr1, Mr2, A1, A2, Vo, Rpm, tp ^{*4} , Htp ^{*4} , R, Rx, AR, Possible Customize						
Graph analysis	Bearing area curve, Amplitude distribution curve						
Filters	Gaussian, 2CR75, PC75						
Cut off length	λ c	0.08, 0.25, 0.8, 2.5 mm					
	λ s ^{*5}	2.5, 8 μm					
Sampling length	0.08, 0.25, 0.8, 2.5 mm						
Number of sampling lengths	x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, arbitrary length (0.3 to 16.0 mm: 0.01 mm interval)				x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, arbitrary length (0.3 to 5.6 mm: 0.01 mm interval)		
LCD dimensions	36.7×48.9 mm						
Display languages	Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian, Turkish, Swedish, Dutch						
Measurement result display	Vertical display: 1-parameter display/3-parameter display/Trace display Horizontal display: 1-parameter display/4-parameter display/Trace display (Horizontal display is invertable)						
Printing function ^{*6} (Dedicated printer is required separately)	Measurement conditions/Calculation results/GO/NG judgement result/Calculation results for each sampling length/ Assessed profile/Bearing area curve/Amplitude distribution curve/Environment setting infomation						
External I/O	USB I/F, Digimatic Output, Printer Output, RS-232C I/F, Foot SW I/F						
Functions	Customization	Desired parameters can be selected for calculation and display					
	GO/NG judgment ^{*7}	By max value/16 %/Standard deviation					
	Storage of measurement condition	Save the conditions at power OFF					
Storage	Internal memory: Measurement condition (10 sets) Memory card (optional): 500 measurement conditions, 10000 measured profiles, 500 display images Text file (Measurement conditions/Measured profile/Assessed profile/ Bearing area curve/Amplitude distribution curve)						
	Calibration	Auto-calibration with the entry of numerical value/ Average calibration with multiple measurement (Max. 5 times) is available					
Power-saving function	Auto-sleep off function (10-600 sec) ^{*8}						
Power supply	Two-way power supply: battery (rechargeable Ni-MH battery) and AC adapter Note 1: Charging time: about 4 hours (may vary due to ambient temperature) Note 2: Endurance: about 1000 measurements (differs slightly due to use conditions/environment)						
Size (W×D×H)	Display unit	52.1×65.8×160 mm (sliding cover closed, detector not mounted)					
	Drive unit	115×23×26 mm (detector not mounted)					
Mass	About 500 g (Display unit + Drive unit + Standard detector)						
Standard accessories	12BAA303 Connecting cable ^{*9} 178-601 Roughness specimen (Ra 3 μm) 12BAR344 Carrying case 12BAK700 Calibration stage Protective sheets for display, AC Adapter, Operation manual, Quick reference manual, Warranty				12BAA303 Connecting cable ^{*9} 178-605 Roughness specimen (Ra 1 μm) 12AAE643 Point-contact adapter 12AAE644 V-type adapter 12BAR344 Carrying case 12BAK700 Calibration stage Protective sheets for display AC Adapter, Operation manual Quick reference manual, Warranty		

*1 Calculation is available only when selecting the VDA, ANSI, or JIS '82 standard.

*2 Calculation is available only when selecting the ISO '97 standard.

*3 Calculation is available only when selecting the JIS '01 standard.

*4 Calculation is available only when selecting the ANSI standard.

*5 Not available when selecting the JIS '82 standard.

*6 Order the **SJ-210** printer (**178-421**, optional accessory) separately.

*7 Standard deviation only can be selected in ANSI. 16 % rule cannot be selected in VDA.

*8 Auto-sleep function is invalid when AC adaptor is used.

*9 For connecting the calculation display unit and drive unit.

Note 1: Refer to pages 18 to 19 for details about consumables and options.


Note 2: To denote your AC line voltage add the following suffixes (e.g. **178-560-11A**).

A for 120 V, C for 100 V, D for 230 V, E for 230 V (for UK), DC for 220 V (for China), K for 220 V (for Korea)


SJ-210 Series Dimensions

- Drive unit stored inside display unit (Standard detector installed in drive unit)

Unit: mm



- Drive unit not stored inside display unit (Standard detector installed in drive unit)



SJ-310 Series Specifications

Type of detector	Standard drive unit type		Retractable drive unit type		Transverse tracing drive unit type		
Model No.	SJ-310 (0.75 mN type)	SJ-310 (4 mN type)	SJ-310 (0.75 mN type)	SJ-310 (4 mN type)	SJ-310 (0.75 mN type)	SJ-310 (4 mN type)	
Order No.	mm	178-570-11	178-570-12	178-572-11	178-572-12	178-574-11	178-574-12
	inch/mm	178-571-11	178-571-12	178-573-11	178-573-12	178-575-11	178-575-12
X axis	16.0 mm				5.6 mm		
Measuring range	Range	360 μm (-200 μm to +160 μm) [14400 μinch (-7900 μinch to +6300 μinch)]					
	Detector Range/resolution	360 μm/0.02 μm 100 μm/0.006 μm 25 μm/0.002 μm					
Measuring speed	When measuring: 0.25 mm/s, 0.5 mm/s, 0.75 mm/s, When returning: 1 mm/s						
Measuring force/Stylus tip	0.75 mN type: 0.75 mN/2 μmR 60°, 4 mN type: 4 mN/5 μmR 90°						
Skid force	400 mN or less						
Applicable standards	JIS '82/JIS '94/JIS '01/ISO '97/ANSI/VDA						
Assessed profiles	Primary profile, Roughness profile, DF profile, Roughness profile-Motif, W-Motif						
Parameters	Ra, Rc, Ry, Rz, Rq, Rt, Rmax ¹ , Rp, Rv, R3z, Rsk, Rku, Rc, R Pc, Rsm, Rz1max ² , S, HSC, RzJIS ³ , Rppi, RΔa, RΔq, Rlr, Rmr, Rmr(c), Rδc, Rk, Rpk, Rvk, Mr1, Mr2, A1, A2, Vo, λa, λq, LO, Rpm, tp ⁴ , Htp ⁴ , R, Rx, AR, W, AW, Wx, Wte, Possible Customize						
Graph analysis	Bearing area curve, Amplitude distribution curve						
Filters	Gaussian, 2CR75, PC75						
Cut-off length	λc	0.08, 0.25, 0.8, 2.5, 8 mm					
	λs ⁵	2.5, 8 μm					
Sampling length	0.08, 0.25, 0.8, 2.5, 8 mm						
Number of sampling lengths	x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, Arbitrary (0.3 to 16.0 mm: 0.01 mm Interval)				x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, Arbitrary (0.3 to 5.6 mm: 0.01 mm Interval)		
LCD dimensions	117.8x88.2 mm						
Display languages	Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian, Turkish, Swedish, Dutch						
Measurement result display	1-parameter display: one parameter measurement result 4-parameter display: four parameter measurement results Profile display: one parameter measurement result and the measured profile Trace display: The ten latest measurement results using the same parameter						
Printing function	Measurement conditions/Calculation results/GO/NG judgement result/Calculation results for each sampling length/Tolerance value/Assessed profile/Graphic curve/Bearing area curve/Amplitude distribution curve/Environmental setting information						
External I/O	USB I/F, Digimatic output, RS-232C I/F, External SW I/F						
Functions	Customization	Desired parameters can be selected for calculation and display					
	GO/NG judgement ⁶	Max rule/16 % rule/Average rule/Standard deviation (1σ, 2σ, 3σ)					
	Storage of measurement condition	Save the condition at power OFF					
	Storage	Internal memory: Measurement condition (10 sets) Memory card (optional): 500 measurement conditions, 10000 measuring data, 500 statistic data, 10000 text data, 1 backup of machine setting, the last ten traces (Trace 10)					
Calibration	Auto-calibration with the entry of numerical value/Average calibration with multiple measurement (Max. 12 times) is available						
Power-saving function	Auto-sleep function (30-600 sec) ⁷						
Power supply	Two-way power supply: battery (rechargeable Ni-MH battery) and AC adapter Note 1: Charging time: about 4 hours (may vary due to ambient temperature) Note 2: Endurance: about 1500 measurements (differs slightly due to use conditions/environment)						
Size (WxDxH)	Display unit	275x109x198 mm					
	Drive unit	115x23x26 mm (detector not mounted)					
Mass	About 1.8 kg (Display unit + Drive unit + Standard detector)						
Standard accessories	12AAW066 Connecting cable ⁸ 178-601 Roughness specimen (Ra 3 μm) 357651 AC adapter 12AAA217 Nosepiece for plane surface 12AAA218 Nosepiece for cylinder 12AAA216 Supporting leg 12BAK700 Calibration stage 12BAR507 Stylus pen 12BAL402 Protection sheet 270732 Printer paper (5 rolls) 12BAL400 Carrying case Philips screwdriver, Strap for stylus pen, Operation manual, Quick reference manual, Warranty				12AAW066 Connecting cable ⁸ 178-605 Roughness specimen (Ra 1 μm) 357651 AC adapter 12AAE643 Point-contact adapter 12AAE644 V-type adapter 12BAK700 Calibration stage 12BAR507 Stylus pen 12BAL402 Protection sheet 270732 Printer paper (5 rolls) 12BAL400 Carrying case Philips screwdriver, Strap for stylus pen, Operation manual, Quick reference manual, Warranty		

*1 Only for VDA/ANSI/JIS '82 standards.

*2 Only for ISO '97 standard.

*3 Only for JIS '01 standard.

*4 Only for ANSI standard.

*5 Not available for JIS '82 standard.

*6 Standard deviation only can be selected in ANSI. 16 % rule cannot be selected in VDA.

*7 Auto-sleep function is invalid when AC adapter is used.

*8 For connecting the calculation display unit and drive unit.


Note 1: Refer to pages 18 to 19 for details about consumables and options.

Note 2: To denote your AC line voltage add the following suffixes (e.g. **178-570-11A**). A for 120 V, C for 100 V, D for 230 V, E for 230 V (for UK), DC for 220 V (for China), K for 220 V (for Korea)

SJ-310 Series Dimensions

• SJ-310 Series Display unit

Unit: mm



• Drive unit

Unit: mm


Drive unit type	Drive unit external view*
Standard drive unit	<p>23.0</p> <p>26.0</p> <p>25.2</p> <p>26.7</p> <p>115.0</p>
Retractable drive unit	<p>23.0</p> <p>26.0</p> <p>2.0</p> <p>23.2</p> <p>26.7</p> <p>115.0</p>
Transverse tracing drive unit	<p>23.0</p> <p>26.0</p> <p>3.0</p> <p>6.6</p> <p>45.5</p> <p>47</p> <p>115.0</p>

* External dimension for the models with standard detector conforms to each drive unit.

Detectors Dimensions

Unit: mm

Standard detectors




Order No.	Measuring force	Stylus form*	Remarks
178-296	0.75 mN	2 $\mu\text{mR}/60^\circ$	Dedicated to the standard/retractable drive unit
178-390	4 mN	5 $\mu\text{mR}/90^\circ$	
178-387	0.75 mN	2 $\mu\text{mR}/60^\circ$	Dedicated to the transverse tracing drive unit
178-386	4 mN	5 $\mu\text{mR}/90^\circ$	
178-391	4 mN	10 $\mu\text{mR}/90^\circ$	Dedicated to the standard/retractable drive unit

• Minimum measurable hole diameter
 Hole depth=less than 12 mm: $\phi 7$ mm
 Hole depth=12 - 22 mm: $\phi 12$ mm

* Tip radius/Tip angle


Gear-tooth surface detectors



Order No.	Measuring force	Stylus form*
178-388	0.75 mN	2 $\mu\text{mR}/60^\circ$
178-398	4 mN	5 $\mu\text{mR}/60^\circ$

* Tip radius/Tip angle


Small hole detectors



Order No.	Measuring force	Stylus form*	Remarks
178-383	0.75 mN	2 $\mu\text{mR}/60^\circ$	Minimum measurable hole diameter: $\phi 4.5$ mm
178-392	4 mN	5 $\mu\text{mR}/90^\circ$	

* Tip radius/Tip angle


Deep groove detectors



Order No.	Measuring force	Stylus form*	Remarks
178-385	0.75 mN	2 $\mu\text{mR}/60^\circ$	Not available for the transverse tracing drive unit
178-394	4 mN	5 $\mu\text{mR}/90^\circ$	

* Tip radius/Tip angle

Extra small hole detectors



Order No.	Measuring force	Stylus form*	Remarks
178-384	0.75 mN	2 $\mu\text{mR}/60^\circ$	Minimum measurable hole diameter: $\phi 2.8$ mm
178-393	4 mN	5 $\mu\text{mR}/90^\circ$	

* Tip radius/Tip angle

How to identify the stylus tip radius



Nose mounting screw (2 pcs.)
 Black : 2 μm
 White : 5 μm
 Yellow: 10 μm

Custom-made for special order

Any specified detector other than above listed can be custom-made for special order. Please consult your local Mitutoyo sales office.

Optional Accessories for SJ-210 Series

- Optional accessories and consumables for **SJ-210**
 Protective sheet for the color LCD (5-sheet set) **12AAL066**
 Connecting cable (for SJ-210 Series) **12AAL067**

Optional Accessories for SJ-310 Series

- Optional accessories and consumables for **SJ-310**
 Printer paper standard type (5 rolls) **270732**
 Durable printer paper (5 rolls) **12AAA876**
 Touch-screen protector sheet (10 sheets) **12AAN040**
 Connecting cable (for SJ-310 Series) **12AAA882**



Optional Accessories for SJ-210/310 Series

• Drive unit accessories

Nosepiece for flat surfaces



12AAA217

Note 1: Standard accessory for the standard/retractable drive unit of the SJ-310 Series
Note 2: Not available for the transverse tracing drive unit.


Nosepiece for cylindrical surfaces



12AAA218

Note 1: Standard accessory for the standard/retractable drive unit of the SJ-310 Series
Note 2: Not available for the transverse tracing drive unit.


Support feet set



12AAA216

Note 1: Standard accessory for the standard/retractable drive unit of the SJ-310 Series
Note 2: Not attachable to the detector side of the transverse tracing drive unit.


V-type adapter



12AAE644

Note 1: Transverse tracing type standard accessory.
Note 2: Dedicated to the transverse tracing drive unit.


Point-contact adapter



12AAE643

Note 1: Transverse tracing type standard accessory.
Note 2: Dedicated to the transverse tracing drive unit.


Extension rod (50 mm)



12AAA210

Note: Not available for the transverse tracing drive unit.

Vertical positioning adapter




12AAA219

Note: Not available for the transverse tracing drive unit.


Height gage adapter

Note: Suitable for a height gage holder designed for 9x9 mm section scribers.



12AAA222


Magnetic stand adapter



12AAA221

(Mounting spigot diameter is 8 mm)

Roughness specimen W



178-604

Note: Ra=Approx. 0.4 μm can only be used for stylus tip checking.

Extension cable (1 m)

Note: Only one rod can be used.

12BAA303

Note: For connecting calculation display unit and drive unit.

Magnetic stand adapter

Note: Only one rod can be used.

12AAA220

(Mounting spigot diameter is 9.5 mm)

• Setting attachments

Note: Not available for the transverse tracing drive unit
Enhances measurement efficiency by facilitating the measurement setup of multiple workpieces of the same type and of the hard-to-access sections of a workpiece.

Setting attachment: V type for measuring in the cylinder axis direction

The V-width is adjustable to the cylinder diameter facilitating axial measurement of a wide range of cylinder diameters.

- Adjustable range:
ø5 - ø150 mm

178-033



Setting attachment: Slider type

This attachment is ideal for measuring a flat area of a workpiece that has an indentation or step that makes it difficult to attach the drive unit.

178-034



Setting attachment: Inside diameter type

Greatly facilitates measurement of internal wall surfaces of, for example, a cylinder block.

- Applicable diameter:
ø75 - ø95 mm
- Accessible depth:
30 - 135 mm

178-035



- Custom-made for special order Any specified attachment other than above listed can be custom-made for special order. Please consult your local Mitutoyo sales office.
Example: measurements for crankshaft, cylinder-block bores



Whatever your challenges are, Mitutoyo supports you from start to finish.

Mitutoyo is not only a manufacturer of top quality measuring products but one that also offers qualified support for the lifetime of the equipment, backed up by comprehensive services that ensure your staff can make the very best use of the investment.

Apart from the basics of calibration and repair, Mitutoyo offers product and metrology training, as well as IT support for the sophisticated software used in modern measuring technology. We can also design, build, test and deliver bespoke measuring solutions and even, if deemed cost-effective, take your critical measurement challenges in-house on a sub-contract basis.



Find additional product literature
and our product catalogue

<https://www.mitutoyo.co.jp/global.html>

Our products are classified as regulated items under Japanese Foreign Exchange and Foreign Trade Law. Please consult us in advance if you wish to export our products to any other country. If the purchased product is exported, even though it is not a regulated item (Catch-All controls item), the customer service available for that product may be affected. If you have any questions, please consult your local Mitutoyo sales office.

Note: Product illustrations are without obligation. Product descriptions, in particular any and all technical specifications, are only binding when explicitly agreed upon.
MITUTOYO and MICAT are either registered trademarks or trademarks of Mitutoyo Corp. in Japan and/or other countries/regions. Other product, company and brand names mentioned herein are for identification purposes only and may be the trademarks of their respective holders.

Mitutoyo

Mitutoyo Corporation

20-1, Sakado 1-Chome,
Takatsu-ku, Kawasaki-shi,
Kanagawa 213-8533, Japan
T +81 (0) 44 813-8230
F +81 (0) 44 813-8231
<https://www.mitutoyo.co.jp>