


TT0281

TT-100KFBD06- /US/

Temperature sensors



L = probe length (corresponds to installation length EL)



Product characteristics

Temperature sensor for connection to a control monitor with a max. operating voltage of 32 V

Quick disconnect

Installation length EL: 100 mm

gold-plated contacts

Connection to control monitor TP / TR

Measuring range: -40...150 °C / -40...302 °F

Measuring element: 1 x Pt 100, to DIN EN 60751, class A

Application

Application liquids and gases

Pressure rating [bar] 160

Minimum installation depth [mm] 15

Electrical data

Connection to control monitor TP / TR

Protection class III

Measuring / setting range

Measuring range -40...150 °C -40...302 °F

Accuracy / deviations

Accuracy ± (0.15 K + 0.002 x |t|)

Reaction times

Dynamic response T05 / T09 [s] 1 / 3 *)

Environment

Ambient temperature [°C] -25...80

Storage temperature [°C] -40...100

Protection IP 68 / IP 69K

Tests / approvals

Shock resistance DIN EN 60068-2-27 50 g (11 ms)

Vibration resistance DIN EN 60068-2-6 10 g (10...2000 Hz)

MTTF [Years] 22831

Mechanical data

Materials (wetted parts) stainless steel 316L / 1.4404

Probe diameter [mm] 6

Probe length L [mm] 100

Installation length EL [mm] 100

Housing materials stainless steel 316L / 1.4404

Weight [kg] 0.032

Electrical connection


Connection M12 connector; gold-plated contacts

TT0281

TT-100KFBD06- /US/

Temperature sensors

Wiring



Remarks

Remarks

cULus - Class 2 source required
*) according to DIN EN 60751
The values for accuracy apply to flowing water.

Pack quantity

[piece]

1