



NMLGB

- flat dome
- for Ba9S LED's

Data

Ordering data

Product type description	NMLGB
Article number (order number)	101174520
EAN (European Article Number)	4250116201396
eCl@ss number, Version 9.0	27-37-12-11

Certifications

Certificates	cULus IPA
--------------	--------------

General data

Product name	NML - Illuminated signal
Standards	EN 60947-5-1 IEC/EN 60947-1
Versions	LED - Indicator light - Front plate mounting Round Flat dome
Installation conditions (mechanical)	arbitrarily Membrane
Sealing type	Lip gaskets Form seals
Material of the dome	PA (12)
Material of the front ring	ABS, chrome-plated
Colour of the dome	Yellow
Colour of the front ring	Silver
Gross weight	30 g

General data - Features

Illuminable	Yes
Mounting flange	Yes
Fully insulated	Yes

Mechanical data

Mounting	Mounting flange ELM
Tightening torque of the screw	0.6 Nm

Mechanical data - Dimensions

Diameter total	44.5 mm
Height of the dome	2 mm
Diameter of the dome	26 mm
Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22.3 + 0.4 mm
Thickness, of the front panel, minimum	1.5 mm
Thickness of the front panel, maximum	6 mm
Spacing	50 x 50 mm

Ambient conditions

Protection class	IP67 IP69K
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C

Status indication

Note (Integral System Diagnostics, status)	for 24 VAC/DC
---	---------------

Scope of delivery

Note (included in delivery, number and type)	Mounting flange ELM is included in delivery
--	---

Documents

Operating instructions and Declaration of conformity

(1,3 MB, 10.05.2019, Revision B)

BG-test certificate

(286,7 kB, 28.04.2020)

UL Certificate

(413,7 kB, 01.08.2019)

IPA Data

(242,8 kB, 10.05.2019, Revision A)

Brochure

(8,7 MB, 10.05.2019, Revision 03)

Pictures

Product picture (catalogue individual photo)



ID: knm--f03

| 37,3 kB | .png | 74.083 x 66.322 mm - 210 x 188


Pixel - 72 dpi

| 433,3 kB | .jpg | 352.778 x 316.794 mm - 1000 x 898

Pixel - 72 dpi

| 60,2 kB | .jpg | 23.223 x 20.828 mm - 320 x 287 Pixel
- 350 dpi

Dimensional drawing basic component



ID: knml-g01

| 64,3 kB | .jpg | 352.778 x 186.267 mm - 1000 x 528

Pixel - 72 dpi

| 2,2 kB | .png | 74.083 x 39.158 mm - 210 x 111 Pixel
- 72 dpi

| 19,7 kB | .cdr |

| 18,9 kB | .jpg | 112.889 x 59.619 mm - 320 x 169

Pixel - 72 dpi

System components

Light terminal block EL




101006534 ELE230

- not suitable for operation with filament lamp or glow lamp



101006529 ELE

- Print with LED symbol



101167368 ELEK

- Print with LED symbol



101167385 ELDEKWS24

- Cage clamps
- Mounting flange position 3
- white LED
- 24 VAC/DC



101167382 ELDEKGB24

- Cage clamps
- Mounting flange position 3
- yellow LED
- 24 VAC/DC

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 23.06.2020 12:58:58