



1) Sensing surface



### Basic features

<b>Approval/Conformity</b>	CE cULus EAC WEEE
<b>Basic standard</b>	IEC 60947-5-2

### Display/Operation

<b>Function indicator</b>	no
<b>Power indicator</b>	no

### Electrical connection

<b>Connection</b>	M8x1-Male, 3-pin
<b>Polarity reversal protected</b>	yes
<b>Protection against device mix-ups</b>	yes
<b>Short-circuit protection</b>	yes

### Electrical data

<b>Load capacitance max. at Ue</b>	0.2 µF
<b>Min. operating current I<sub>m</sub></b>	1 mA
<b>No-load current I<sub>o</sub> max., damped</b>	9 mA
<b>No-load current I<sub>o</sub> max., undamped</b>	3 mA
<b>Operating voltage U<sub>b</sub></b>	10...30 VDC
<b>Output resistance R<sub>a</sub></b>	Open collector
<b>Rated insulation voltage U<sub>i</sub></b>	75 V DC
<b>Rated operating current I<sub>e</sub></b>	150 mA
<b>Rated operating voltage U<sub>e</sub> DC</b>	24 V
<b>Rated short circuit current</b>	100 A
<b>Ready delay t<sub>v</sub> max.</b>	20 ms
<b>Residual current I<sub>r</sub> max.</b>	10 µA
<b>Ripple max. (% of U<sub>e</sub>)</b>	10 %
<b>Switching frequency</b>	3000 Hz
<b>Utilization category</b>	DC -13
<b>Voltage drop static max.</b>	2.5 V

### Environmental conditions

<b>Ambient temperature</b>	-25...70 °C
<b>Contamination scale</b>	3
<b>EN 60068-2-27, Shock</b>	Half-sinus, 30 g <sub>n</sub> , 11 ms
<b>EN 60068-2-6, Vibration</b>	55 Hz, amplitude 1 mm, 3x30 min
<b>IP rating</b>	IP67

### Functional safety

<b>MTTF (40 °C)</b>	830 a
---------------------	-------

Inductive Sensors  
**BES M08EA-PSD15B-S49G**  
Order Code: BES0277



**Interface**

Switching output PNP normally open (NO)

**Material**

Housing material Stainless steel  
Material sensing surface PBT

**Mechanical data**

Dimension Ø 8 x 18 mm  
Installation for flush mounting  
Size M8x1  
Tightening torque 4 Nm

**Range/Distance**

Assured operating distance Sa 1.2 mm  
Hysteresis H max. (% of Sr) 15.0 %  
Rated operating distance Sn 1.5 mm  
Real switching distance sr 1.5 mm  
Repeat accuracy max. (% of Sr) 5.0 %  
Temperature drift max. (% of Sr) 10 %  
Tolerance Sr ±10 %

**Remarks**

For mounting and installation see Accessories section  
EMC: EMC protection circuit required, see 825345. IVW: 2.2  
The sensor is functional again after the overload has been eliminated.  
For more information about MTTf and B10d see MTTf / B10d Certificate

Indication of the MTTf- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

**Connector Drawings**



**Wiring Diagrams**

